




FLIR TA90

Dual Male and Female MC4 Test Leads with Banana Plug

www.flir.com/TA90



Key Features

- Equipped with MC4 PV plugs for easy parallel connection with solar panels
- Safely measures up to 1500 V with CAT III rated MC4 PV plugs
- Creates MC4 connection between solar panel and inverter for troubleshooting and maintenance of PV systems
- Ensures safe current and voltage measurements on Photovoltaic (PV) modules and systems

Main Applications

- Verify the performance and safety of solar power systems
- Ensure the quality of solar panels during production

SPECIFICATIONS

	FLIR TA90
Length	152 cm (60 in)
Connectors	Dual MC4 (both male and female) to 4 mm sheathed banana plugs
Voltage rating	Up to 1500 V with CAT III rated dual MC4 PV plugs
Functionality	Creates MC4 connection between solar panel & inverter in parallel
Safety features	Ensures safe current & voltage measurements on PV modules
Related products	CM78-PV, PV-KIT-1, PV-KIT-2
What's included?	Dual PV test leads
Warranty	Limited 3-Year Warranty

Specifications subject to change. For the most up-to-date specifications, please visit flir.com.

For technical or sales support, please visit:
www.flir.com/about/general-inquiries

This product is subject to United States export regulations and may require US authorization prior to export, reexport, or transfer to non-US persons or parties. Diversion contrary to US law is prohibited.

For assistance with confirming the Jurisdiction & Classification of Teledyne FLIR, LLC products, please contact exportquestions@flir.com. ©2025 Teledyne FLIR, LLC. All rights reserved.

Revised 02/27/25
FLIR_TA90_Datasheet_en-GB-A4 RH24-0864-INS