



Option, No radio

P/N: T300030

Copyright

© 2025, FLIR Systems, Inc.

All rights reserved worldwide. Names and marks appearing herein are either registered trademarks or trademarks of FLIR Systems and/or its subsidiaries. All other trademarks, trade names or company names referenced herein are used for identification only and are the property of their respective owners.

Document identity

Publ. No.: T300030

Release: AB

Commit: 103806

Language: en-US

Modified: 2025-04-08

Formatted: 2025-04-08

Website

<http://www.flir.com>

Customer support

<http://support.flir.com>

Disclaimer

Specifications subject to change without further notice. Camera models and accessories subject to regional market considerations. License procedures may apply. Products described herein may be subject to US Export Regulations. Please refer to exportquestions@flir.com with any questions.

General description

With this option, the following features in the camera are configured to be permanently disabled:

- WiFi
- Bluetooth
- GPS

Compatible with the following products:

- 13901-0101; FLIR G304 14.5°
- 13901-0102; FLIR G304 24°
- 13801-0101; FLIR G306 14.5°
- 13801-0102; FLIR G306 24°
- 10801-0101; FLIR G343 14.5°
- 10801-0102; FLIR G343 24°
- 10901-0101; FLIR G346 14.5°
- 10901-0102; FLIR G346 24°
- 15902-0101; FLIR G609 24° Furnace lens
- 15901-0101; FLIR G609 24° Standard lens
- 10301-0102; FLIR G615 20°
- 10501-0101; FLIR G620 14.5°
- 10501-0102; FLIR G620 24°
- 10701-0101; FLIR G635 14.5°
- 10701-0102; FLIR G635 24°
- 10401-0101; FLIR Gx320 14.5°
- 10401-0102; FLIR Gx320 24°
- 10601-0101; FLIR Gx620 14.5°
- 10601-0102; FLIR Gx620 24°
- 72502-0501; FLIR T1010 12°
- 72502-0502; FLIR T1010 28°
- 72502-0503; FLIR T1010 45°
- 72501-0101; FLIR T1020 12°
- 72501-0102; FLIR T1020 28°
- 72501-0104; FLIR T1020 28° and 12°
- 72501-0105; FLIR T1020 28° and 45°
- 72501-0106; FLIR T1020 28°, 12°, and 45°
- 72501-0103; FLIR T1020 45°
- 72501-0201; FLIR T1030sc 12°
- 72501-0202; FLIR T1030sc 28°
- 72501-0203; FLIR T1030sc 45°
- 72501-0301; FLIR T1040 12°
- 72501-0302; FLIR T1040 28°
- 72501-0303; FLIR T1040 45°
- 72501-0401; FLIR T1050sc 12°
- 72501-0402; FLIR T1050sc 28°
- 72501-0403; FLIR T1050sc 45°
- 79301-0101; FLIR T530 14°
- 79302-0101; FLIR T530 24°
- 79304-0101; FLIR T530 24° + 14°
- 79306-0101; FLIR T530 24° + 14° & 42°
- 79305-0101; FLIR T530 24° + 42°
- 79303-0101; FLIR T530 42°
- 79307-0101; FLIR T530 42° + 14°
- 79309-0101; FLIR T530 80°
- 79308-0101; FLIR T530 Dual FOV 14° + 24°
- 79310-0101; FLIR T530 Dual FOV 42° + 24°
- 79301-0201; FLIR T540 14°
- 79302-0201; FLIR T540 24°
- 79304-0201; FLIR T540 24° + 14°
- 79306-0201; FLIR T540 24° + 14° & 42°

P/N: T300030

© 2025, FLIR Systems, Inc.

#T300030; r. AB/103806; en-US

- 79305-0201; FLIR T540 24° + 42°
- 79303-0201; FLIR T540 42°
- 79307-0201; FLIR T540 42° + 14°
- 79309-0201; FLIR T540 80°
- 79308-0201; FLIR T540 Dual FOV 14° + 24°
- 79310-0201; FLIR T540 Dual FOV 42° + 24°
- 89001-0101; FLIR T560 14°
- 89002-0101; FLIR T560 24°
- 89004-0101; FLIR T560 24° + 14°
- 89006-0101; FLIR T560 24° + 14° & 42°
- 89005-0101; FLIR T560 24° + 42°
- 89003-0101; FLIR T560 42°
- 89007-0101; FLIR T560 42° + 14°
- 89010-0101; FLIR T560 80°
- 89009-0101; FLIR T560 Dual FOV 14° + 24°
- 89011-0101; FLIR T560 Dual FOV 42° + 24°
- 82501-0201; FLIR T840 14°
- 82502-0201; FLIR T840 24°
- 82504-0201; FLIR T840 24° + 14°
- 82506-0201; FLIR T840 24° + 14° & 42°
- 82509-0201; FLIR T840 24° + 14° & 6°
- 82505-0201; FLIR T840 24° + 42°
- 82508-0201; FLIR T840 24° + 6°
- 82503-0201; FLIR T840 42°
- 82507-0201; FLIR T840 42° + 14°
- 82511-0201; FLIR T840 80°
- 82510-0201; FLIR T840 Dual FOV 14° + 24°
- 82512-0201; FLIR T840 Dual FOV 42° + 24°
- 89201-0101; FLIR T860 14°
- 89202-0101; FLIR T860 24°
- 89204-0101; FLIR T860 24° + 14°
- 89206-0101; FLIR T860 24° + 14° & 42°
- 89211-0101; FLIR T860 24° + 14° & 6°
- 89205-0101; FLIR T860 24° + 42°
- 89210-0101; FLIR T860 24° + 6°
- 89203-0101; FLIR T860 42°
- 89207-0101; FLIR T860 42° + 14°
- 89212-0101; FLIR T860 Dual FOV 14° + 24°
- 89214-0101; FLIR T860 Dual FOV 42° + 24°
- 89201-0201; FLIR T865 14°
- 89202-0201; FLIR T865 24°
- 89204-0201; FLIR T865 24° + 14°
- 89206-0201; FLIR T865 24° + 14° & 42°
- 89213-0201; FLIR T865 24° + 14° & 6°
- 89205-0201; FLIR T865 24° + 42°
- 89212-0201; FLIR T865 24° + 6°
- 89203-0201; FLIR T865 42°
- 89207-0201; FLIR T865 42° + 14°
- 89215-0201; FLIR T865 80°
- 89214-0201; FLIR T865 Dual FOV 14° + 24°
- 89216-0201; FLIR T865 Dual FOV 42° + 24°
- 84502-0301; FLIR E52 24°
- 84512-1201; FLIR E54 24°
- 78511-1101; FLIR E76 14°
- 78512-1101; FLIR E76 24°
- 78514-1101; FLIR E76 24° + 14°
- 78516-1101; FLIR E76 24° + 14° & 42°
- 78515-1101; FLIR E76 24° + 42°
- 78513-1101; FLIR E76 42°



Option, No radio

P/N: T300030

© 2025, FLIR Systems, Inc.

#T300030; r. AB/103806; en-US

- 78517-1101; FLIR E76 42° + 14°
- 78519-1101; FLIR E76 80°
- 78518-1101; FLIR E76 Dual FOV 14° + 24°
- 78521-1101; FLIR E76 Dual FOV 42° + 24°
- 78523-1101; FLIR E76 Dual FOV 42° + 24° + 14°
- 78511-1301; FLIR E86 14°
- 78512-1301; FLIR E86 24°
- 78514-1301; FLIR E86 24° + 14°
- 78516-1301; FLIR E86 24° + 14° & 42°
- 78515-1301; FLIR E86 24° + 42°
- 78513-1301; FLIR E86 42°
- 78517-1301; FLIR E86 42° + 14°
- 78519-1301; FLIR E86 80°
- 78518-1301; FLIR E86 Dual FOV 14° + 24°
- 78523-1301; FLIR E86 Dual FOV 42° + 24°
- 78521-1301; FLIR E86 Dual FOV 42° + 24° + 14°
- 90201-0101; FLIR E96 14°
- 90202-0101; FLIR E96 24°
- 90204-0101; FLIR E96 24° + 14°
- 90206-0101; FLIR E96 24° + 14° & 42°
- 90205-0101; FLIR E96 24° + 42°
- 90203-0101; FLIR E96 42°
- 90207-0101; FLIR E96 42° + 14°
- 90209-0101; FLIR E96 80°
- 90208-0101; FLIR E96 Dual FOV 14° + 24°
- 90212-0101; FLIR E96 Dual FOV 42° + 24°
- 90223-0101; FLIR E96 Dual FOV 42° + 24° + 14°