

P/N: T911706ACC

Copyright

© 2025, FLIR Systems, Inc.

All rights reserved worldwide. Names and marks appearing herein are either registered trademarks or trademarks of FLIR Systems and/or its subsidiaries. All other trademarks, trade names or company names referenced herein are used for identification only and are the property of their respective owners.

Document identity

Publ. No.: T911706ACC

Release: AD

Commit: 103172

Language: en-US

Modified: 2025-03-19

Formatted: 2025-03-19

Website

<http://www.flir.com>

Customer support

<http://support.flir.com>

Disclaimer

Specifications subject to change without further notice. Camera models and accessories subject to regional market considerations. License procedures may apply. Products described herein may be subject to US Export Regulations. Please refer to exportquestions@flir.com with any questions.



General description

This cable is used to power the infrared camera from the cigarette lighter socket in a car. Requires a USB Type-C to USB Type-C cable (USB 2.0 standard), T911705ACC.

Physical data

Weight	18 g (0.63 oz.)
Connector	USB Type-A, USB Type-C

Shipping information

Packaging, type	Cardboard box
List of contents	• Car adapter
Packaging, weight	
Packaging, size	
EAN-13	4743254003095
UPC-12	845188014490
Country of origin	Estonia

Compatible with the following products:

- 85201-0102; FLIR GF77 LR 25°
- 85202-0102; FLIR GF77 HR 25°
- 85203-0102; FLIR GF77 LR 25° + HR 25°
- 85204-0102; FLIR GF77 LR 25° + LR 6°
- 85205-0102; FLIR GF77 HR 25° + HR 6°
- 85206-0102; FLIR GF77 LR 25° + HR 25° + HR 6°
- 85207-0102; FLIR GF77 LR 25° + HR 25° + LR 6°
- 85208-0102; FLIR GF77 LR 25° + HR 25° + LR 6° + HR 6°
- 79301-0101; FLIR T530 14°
- 79302-0101; FLIR T530 24°
- 79304-0101; FLIR T530 24° + 14°
- 79306-0101; FLIR T530 24° + 14° & 42°
- 79305-0101; FLIR T530 24° + 42°
- 79303-0101; FLIR T530 42°
- 79307-0101; FLIR T530 42° + 14°
- 79309-0101; FLIR T530 80°
- 79308-0101; FLIR T530 Dual FOV 14° + 24°
- 79310-0101; FLIR T530 Dual FOV 42° + 24°
- 79301-0201; FLIR T540 14°
- 79302-0201; FLIR T540 24°
- 79304-0201; FLIR T540 24° + 14°
- 79306-0201; FLIR T540 24° + 14° & 42°
- 79305-0201; FLIR T540 24° + 42°
- 79303-0201; FLIR T540 42°

P/N: T911706ACC

© 2025, FLIR Systems, Inc.

#T911706ACC; r. AD/103172; en-US

- 79307-0201; FLIR T540 42° + 14°
- 79309-0201; FLIR T540 80°
- 79308-0201; FLIR T540 Dual FOV 14° + 24°
- 79310-0201; FLIR T540 Dual FOV 42° + 24°
- 89001-0101; FLIR T560 14°
- 89002-0101; FLIR T560 24°
- 89004-0101; FLIR T560 24° + 14°
- 89006-0101; FLIR T560 24° + 14° & 42°
- 89005-0101; FLIR T560 24° + 42°
- 89003-0101; FLIR T560 42°
- 89007-0101; FLIR T560 42° + 14°
- 89010-0101; FLIR T560 80°
- 89009-0101; FLIR T560 Dual FOV 14° + 24°
- 89011-0101; FLIR T560 Dual FOV 42° + 24°
- 82501-0201; FLIR T840 14°
- 82502-0201; FLIR T840 24°
- 82504-0201; FLIR T840 24° + 14°
- 82506-0201; FLIR T840 24° + 14° & 42°
- 82509-0201; FLIR T840 24° + 14° & 6°
- 82505-0201; FLIR T840 24° + 42°
- 82508-0201; FLIR T840 24° + 6°
- 82503-0201; FLIR T840 42°
- 82507-0201; FLIR T840 42° + 14°
- 82511-0201; FLIR T840 80°
- 82510-0201; FLIR T840 Dual FOV 14° + 24°
- 82512-0201; FLIR T840 Dual FOV 42° + 24°
- 89201-0101; FLIR T860 14°
- 89202-0101; FLIR T860 24°
- 89204-0101; FLIR T860 24° + 14°
- 89206-0101; FLIR T860 24° + 14° & 42°
- 89211-0101; FLIR T860 24° + 14° & 6°
- 89205-0101; FLIR T860 24° + 42°
- 89210-0101; FLIR T860 24° + 6°
- 89203-0101; FLIR T860 42°
- 89207-0101; FLIR T860 42° + 14°
- 89212-0101; FLIR T860 Dual FOV 14° + 24°
- 89214-0101; FLIR T860 Dual FOV 42° + 24°
- 89201-0201; FLIR T865 14°
- 89202-0201; FLIR T865 24°
- 89204-0201; FLIR T865 24° + 14°
- 89206-0201; FLIR T865 24° + 14° & 42°
- 89213-0201; FLIR T865 24° + 14° & 6°
- 89205-0201; FLIR T865 24° + 42°
- 89212-0201; FLIR T865 24° + 6°
- 89203-0201; FLIR T865 42°
- 89207-0201; FLIR T865 42° + 14°
- 89215-0201; FLIR T865 80°
- 89214-0201; FLIR T865 Dual FOV 14° + 24°
- 89216-0201; FLIR T865 Dual FOV 42° + 24°
- 84502-0301; FLIR E52 24°
- 84512-1201; FLIR E54 24°
- 78511-1101; FLIR E76 14°
- 78512-1101; FLIR E76 24°
- 78514-1101; FLIR E76 24° + 14°
- 78516-1101; FLIR E76 24° + 14° & 42°
- 78515-1101; FLIR E76 24° + 42°
- 78513-1101; FLIR E76 42°
- 78517-1101; FLIR E76 42° + 14°
- 78519-1101; FLIR E76 80°



Car adapter 12V

P/N: T911706ACC

© 2025, FLIR Systems, Inc.

#T911706ACC; r. AD/103172; en-US

- 78518-1101; FLIR E76 Dual FOV 14° + 24°
- 78521-1101; FLIR E76 Dual FOV 42° + 24°
- 78523-1101; FLIR E76 Dual FOV 42° + 24° + 14°
- 78511-1301; FLIR E86 14°
- 78512-1301; FLIR E86 24°
- 78514-1301; FLIR E86 24° + 14°
- 78516-1301; FLIR E86 24° + 14° & 42°
- 78515-1301; FLIR E86 24° + 42°
- 78513-1301; FLIR E86 42°
- 78517-1301; FLIR E86 42° + 14°
- 78519-1301; FLIR E86 80°
- 78518-1301; FLIR E86 Dual FOV 14° + 24°
- 78523-1301; FLIR E86 Dual FOV 42° + 24°
- 78521-1301; FLIR E86 Dual FOV 42° + 24° + 14°
- 90201-0101; FLIR E96 14°
- 90202-0101; FLIR E96 24°
- 90204-0101; FLIR E96 24° + 14°
- 90206-0101; FLIR E96 24° + 14° & 42°
- 90205-0101; FLIR E96 24° + 42°
- 90203-0101; FLIR E96 42°
- 90207-0101; FLIR E96 42° + 14°
- 90209-0101; FLIR E96 80°
- 90208-0101; FLIR E96 Dual FOV 14° + 24°
- 90212-0101; FLIR E96 Dual FOV 42° + 24°
- 90223-0101; FLIR E96 Dual FOV 42° + 24° + 14°