



Measure motor winding resistance and other low resistances

Product features

MMR-630/620 microohmmeters enable accurate measurements of both connections resistance (welded, soldered, bolted) and winding resistance of electrical motors.

- Measurements of objects resistive in nature:
 - » welded and soldered connections, equipotential bondings, earthing conductors,
 - » contacts, welds of rails, conductors and cables,
 - » measurement according to the four-lead method.
- Measurements of objects inductive in nature:
 - » motor windings,
 - » low-resistance coils.



Additional functions

- Automatic or manual selection of measuring range (measurement of objects of an inductive nature).
- Selection of measurement mode according to the type of measured object:
 - » fast measurement (3 seconds) for measurement of objects of a resistive nature,
 - » extended measurement for testing of objects of an inductive nature (accelerated mode, with slightly worse accuracy, available); with automatic discharging of the object after measurement.
- Selection of measurement mode depending on application (including control of product series):
 - » measurement in **normal** mode - triggered when the "START" button is pressed,
 - » measurement in **automatic** mode - the instrument awaits connection of all four test leads to the object, after which it automatically start measurement in one or both directions and calculates the mean resistance value,
 - » measurement in **continuous** mode - the meter repeats successive measurement cycles with breaks every 3 seconds (for objects of a resistive nature) or performs measurement continuously (for objects of an inductive nature).
- Window mode:
 - » makes possible to set an upper and lower limit within the measurement result should remain; sound signal triggered when the result is beyond set range,
 - » capability of performing measurements even under disturbances of a value five times greater than the measured signal.

Resistance measurement

MMR-620		MMR-630		Test current	Accuracy
Range	Resolution	Range	Resolution		
0...999 $\mu\Omega$ *	1 $\mu\Omega$	0...999.9 $\mu\Omega$	0.1 $\mu\Omega$		
1.000...1.999 m Ω	0.001 m Ω	1.0000...1.9999 m Ω	0.0001 m Ω	10 A	
2.00...19.99 m Ω	0.01 m Ω	2.000...19.999 m Ω	0.001 m Ω		
20.0...199.9 m Ω	0.1 m Ω	20.00...199.99 m Ω	0.01 m Ω	1 A	
200...999 m Ω	1 m Ω	200...999.9 m Ω	0.1 m Ω		$\pm(0.25\% \text{ m.v.} + 2 \text{ digits})$
1.000...1.999 Ω	0.001 Ω	1.0000...1.9999 Ω	0.0001 Ω	0.1 A	
2.00...19.99 Ω	0.01 Ω	2.000...19.999 Ω	0.001 Ω	10 mA	
20.0...199.9 Ω	0.1 Ω	20.00...199.99 Ω	0.01 Ω	1 mA	
200...1999 Ω	1 Ω	200.0...1999.9 Ω	0.1 Ω	0.1 mA	



*„m.v.” - measured value

Technical specification

insulation type acc. to EN 61010-1	double	
measurement category acc. to EN 61010-2-030	III 300 V	
ingress protection acc. to EN 60529	IP54	
protection against external voltage	up to 440 V AC for 10 s	
power supply to battery charger	100 V...250 V/50 Hz...60 Hz, 200 mA	
battery charging time	ca. 2.5 h	
number of measurements with 10 A current performed when powered from the battery pack	300	
maximum wire resistance for 10 A current	0.1 Ω	
accuracy of measuring current setting	$\pm 10\%$	
time of performing the resistance measurement	with selected resistive object type and bidirectional current flow	3 s
	with selected inductive object type, dependent on the resistance and inductance of the object	couple of minutes (max. 10)
dimensions	295 x 222 x 95 mm 11.6" x 8.7" x 3.7"	
meter weight	ca. 1.7 kg ca. 3.7 lbs	
operating temperature	0°C...40°C 32°F...104°F	
charger operating temperature	10°C...35°C 50°F...95°F	
storage temperature	-20°C...+60°C -4°F...+140°F	
humidity	20%...90%	
reference temperature	23°C \pm 2°C 73.4°F \pm 3.6°F	
reference humidity	40%...60%	
temperature coefficient	$\pm 0,01\%$ d.v./°C	
time to AUTO-OFF	120 s	
TFT graphic display	192 x 64 pixels	
interface standard	RS-232C	
quality standard - design and manufacturing	ISO 9001	
the product meets the EMC requirements (emission for industrial environment) according to	EN 61326-1 and EN 61326-2-2	

"d.v." - displayed value

Standard accessories




**2 x Kelvin clamp
1 kV 25 A**
WAKROKELK06



**4x crocodile clip
black 1 kV 32 A**
WAKROBL30K03



**2x double-tip
Kelvin probe
(banana sockets)**
WASONKEL20GB



**Doble-wire test lead
3 m (10 / 25 A)**
U1/I1
WAPRZ003DZBBU111
U2/I2
WAPRZ003DZBBU212



**Mains power cable
Euro 2-pin plug
/ IEC C7 plug**
WAPRZLAD230



**NiMH battery
4.8 V 3.2 Ah**
WAAKU03



**Unisonel hanging
straps**
WAPOZSZE1



L1 carrying case
WAFUTL1



**RS-232 serial
transmission cable**
WAPRZRS232



**Factory calibra-
tion certificate**

Optional accessories



**Double-wire test lead
(10 A / 25 A) U1/I1
6 m / 10 m / 15 m**
WAPRZ006DZBBU111
WAPRZ010DZBBU111
WAPRZ015DZBBU111



**Double-wire test lead
(10 A / 25 A) U2/I2
6 m / 10 m / 15 m**
WAPRZ006DZBBU212
WAPRZ010DZBBU212
WAPRZ015DZBBU212



**Kelvin vice
with cables**
WAZACKEL1



USB/RS-232 adapter
WAADAUSBRS232



**Sonel Reader
software**
WAPROREADER



**Calibration certificate
with accreditation**