



| Specification   | Range                     | UT60EU    | UT60BT |
|---|---------------------------|-----------|--------|
| <b>Certificates</b>                                     |                           |           |        |
|   | CE, UKCA, cETLus          |           |        |
| DC voltage (V)  | 1000V                     | ±(0.5%+3) |        |
| AC voltage (V)  | 1000V                     | ±(0.8%+3) |        |
| DC current (A)  | 10A                       | ±(0.8%+3) |        |
| AC current (A)  | 10A                       | ±(1.0%+3) |        |
| Resistance (Ω)  | 100MΩ                     | ±(0.8%+2) |        |
| Capacitor (F)   | 10mF                      | ±(4.0%+5) |        |
| Frequency (Hz)  | 99.99Hz~9.999MHz          | ±(0.1%+5) |        |
| Duty cycle (%)  | 0.1~99.9%                 | ±(3%+5)   |        |
| Temperature (°C/°F)                                     | -40°C~1000°C/-40°F~1832°F | ±4°C/±5°F |        |
| <b>Features</b>   |                           |           |        |
| Bluetooth   | UT60BT only               |           |        |
| Display count   | 9999                      |           |        |
| Auto range  | √                         |           |        |
| REL   | √                         |           |        |
| NCV   | √                         |           |        |
| Diode   | √                         |           |        |
| Continuity test   | √                         |           |        |
| Acousto-optic indication (NCV/continuity/battery power) | √                         |           |        |
| Low battery indication                                  | ≤3.6V                     |           |        |
| Data hold   | √                         |           |        |
| Auto power off  | 15Min                     |           |        |
| Operating temperature                                   | 0°C~40°C                  |           |        |
| Safety  | CATII 1000V/CATIII 600V   |           |        |

| <b>Characteristics</b>       |                                |
|------------------------------|--------------------------------|
| Battery                      | 1.5V AAA x 3                   |
| Product color                | Red and gray                   |
| Product net weight           | 290g                           |
| Product size                 | 169 x 81 x 46mm                |
| Standard individual packing  | Gift box, manual, thermocouple |
| Standard quantity per carton | 20pcs                          |
| Standard carton size         | 420 x 320 x 300mm              |



UT60BT

UT60BT digital multimeter has a built-in Bluetooth module which can be used with iDMM2.0 app.



- Smart phone APP: iDMM2.0
- Works with UT-D07B Bluetooth adaptor
- Download from App Store or Google Play



UT60EU



UT60S

| Specification       | Range  | Accuracy  |
|---------------------|--|-----------|
| <b>Certificates</b> | <b>CE, UKCA, cETLus</b>  |           |
| DC voltage (V)      | 9.999mV/99.99mV/999.9mV/9.999V/99.99V/999.9V                   | ±(0.5%+3) |
| AC voltage (V)      | 9.999mV/99.99mV/999.9mV/9.999V/99.99V/999.9V                   | ±(0.8%+3) |
| DC current (A)      | 999.9μA/999.9mA/9.999A   | ±(0.8%+3) |
| AC current (A)      | 999.9μA/999.9mA/9.999A   | ±(1.0%+3) |
| Resistance (Ω)      | 99.99Ω/999.9Ω/9.999kΩ/99.99kΩ/999.9kΩ/9.999MΩ/99.99MΩ          | ±(0.8%+2) |
| Capacitance (F)     | 9.999nF/99.99nF/999.9nF/9.999μF/99.99μF/999.9μF/9.999mF/99.9mF | ±(4%+5)   |
| Frequency           | 9.999Hz~9.999MHz   | ±(0.1%+5) |
| Duty cycle          | 0.1~99.9%  | ±(3%+5)   |
| Temperature         | -40°C~1000°C/-40°F~1832°F                                      | ±4°C/±5°F |

| Features   |                         |
|--|-------------------------|
| Display count  | 9999                    |
| Auto range   | √                       |
| NCV  | √                       |
| Diode/REL  | √                       |
| Continuity test  | √                       |
| Acousto-optic indication(NCV/continuity/battery power) | √                       |
| Low battery indication                                 | ≤3.6V                   |
| Data hold  | √                       |
| Auto power off   | 15Min                   |
| Operation temperature                                  | 0°C~40°C                |
| Safety   | CATII 1000V/CATIII 600V |

| General Characteristics      |                                |
|------------------------------|--------------------------------|
| Battery                      | 1.5VAAA x3                     |
| Product color                | Red and Gray                   |
| Product net weight           | 290g                           |
| Product size                 | 169 x 81 x 46mm                |
| Standard individual packing  | Gift Box, Manual, Thermocouple |
| Standard quantity per carton | 20pcs                          |
| Standard carton size         | 420 x 320 x 300mm              |